IMPORTANT: PLEASE RETAIN THIS INSTRUCTION MANUAL FOR FUTURE REFERENCE



Notes to the Technician:

E&G is proud to present this package to you and reminds you that for technical information, contact Lynn Eash or Lee Clary at 410-381-4900. Do not attempt installation any E&G product without first reading the detailed instructions. E&G Classics will not warrant damaged parts or vehicle due to altered installation instructions.

Copyright © 2007 by E&G Classics, Inc.

All right reserved. The reproduction or utilization of this work in any form or any electronic, mechanical, or other means, no known or hereafter invented, including xerography, photocopying, and recording, and in any information storage retrieval system is forbidden without written permission of owners.



Part # 1364-0185-07Q

Quantity	<u>Description</u>		<u>Part</u>	<u>No.</u>
1 Set	Upper Q Inserts			
				8B-07Q
		Bottom Right	1364-01	8Y-07Q
		Bottom Left	1364-01	8Z-07Q
:	Small "E&G Classics" E	Emblem	1999-02	268-00
1	Hardware Kit (compone	ents listed below)	1364-01	84-07Q
4	1.006" x .189" x .064" B	Black Washers	1999-02	264-00
	8-32 ESNA Half Nuts		1999-00	
8	.156" x 1" Vinyl Caps		1999-02	41-00

mentilling

Remove the plastic radiator support panel cover by removing the 10mm hex bolts across the back edge and the torx screws across the front edge.

Apply masking tape to the painted (or chromed) openings of the factory grille (as shown).

IMPORTANT! The edges of the stainless steel grille can be extremely sharp. Please handle with care.

WARRANTY INFORMATION:

E&G Classics, Inc. warrants its chrome parts and products to be free from defects in material, workmanship or finish for Thirty-Six [36] months from the date of shipment by E&G. This warranty is limited to the repair or replacement, at E&G Classics option, of the defective part or product.

To obtain performance under this warranty you must:

- Present your E&G unit to an authorized distributor in your area with proof of purchase. 2. If no distributor is available, contact E&G Classics (address below) for authorization to
- 3. Returns All unauthorized returns will be refused. Merchandise approved by E&G for return must have been purchased within the Thirty-Six (36) months. All returns require an authorization number obtained from E&G and the actual return must be accompanied by the written authorization form filled out completely. All merchandise must be inspected upon receipt and shortages reported within 48 hours. All merchandise must be in a resalable condition. Merchandise must be packed carefully in the original packing. If original packing is no longer usable, repack item(s) comparable to original manner. All returns are subject to a 25% handling charge. Special order items are not returnable. Defective mer chandise must have an explanation of the problem. No credit will be issued unless invoice number and date of purchase has been supplied. Manufacturer shall be sole judge of defects in a product.
- UPS accounts All returns must be prepaid. Do not send return shipments freight col lect. Once E&G has made its decision and it is a claim against our warranty policy, E&G will credit incoming freight on damaged parts
- 5. No discontinued part or parts changed due to body style are returnable.

For Return Authorization, write or telephone: E&G Classics, Inc., 8910 McGaw Court, Columbia, MD 21045 (410) 381-4900 Attn.: Return Department

You are responsible for inspecting all packages containing E&G Classics' parts and product immediately upon their receipt and must file a claim with the carrier for any damage disclosure by such inspection and notify E&G classics in writing at the above address of any such damage. This warranty does not extend to any of our products which have been subject to misuse, neglect, accident or have been altered or repaired in any way. This warranty does not cover any accidental or consequential damages for any breach of this warranty agreement. E&G Classics shall have no responsibility for any loss of time, inconvenience, commercial loss or consequential damage, nor shall E&G be liable for any injury or damage to persons or property by reason of any defect in material, workmanship or finish of its parts or products. This warranty gives you specific legal rights and you may also have other rights which may vary from state to state.

Open the hood and remove the plastic battery cover by turning the attaching pins and lifting out.




Align one of the "Q" grille sections into place and press the outer stud firmly against the plastic to indent it.




Drill the outer stud mounting holes with a 1/4" drill bit.






6. Trim the closed tip from the supplied vinyl caps and install them onto the outer studs welded to the back of the upper "Q" grille sections.




 Remove the protective film from the grille section and clean off the glue residue using a mild solvent or adhesive remover followed with alcohol or glass cleaner.





With the grille in place, remove any protective masking tape that could get could get caught behind the grille section once it is tightened.



10. Tighten the outer ESNA nut, making sure the grille is snug but **DO NOT OVERTIGHTEN**. Overtightening will indent the grille where the studs are attached.



11. Tighten the inner ESNA nut, making sure the grille is snug but **DO NOT OVERTIGHTEN**. Overtightening will indent the grille where the studs are attached.

12. Repeat Steps 4 thru 10 for the remaining grille sections.



13. Finished installation.