IMPORTANT: PLEASE RETAIN THIS INSTRUCTION MANUAL FOR FUTURE REFERENCE



2005-10 Chrysler 300 Ultimate, Heavy Metal, Center Bar, Euro, Dual Weave, Fine Mesh & Billet Grilles Revised 01/24/12

1

Notes to the Technician:

E&G is proud to present this package to you and reminds you that for technical information, contact Lynn Eash or Lee Clary at 410-381-4900. Do not attempt installation any E&G product without first reading the detailed instructions. E&G Classics will not warrant damaged parts or vehicle due to altered installation instructions.

Copyright © 2005 by E&G Classics, Inc. All right reserved. The reproduction or utilization of this work in any form or any electronic, mechanical, or other means, no known or hereafter invented, including xerography, photocopying, and recording, and in any information storage retrieval system is forbidden without written permission of owners.



"Heavy Metal" Part # 1099-0104-05R

Quantity	<u>Description</u>	<u>Part No.</u>
1	Mesh Grille Insert (includes)	********
	Chrome Plated Surround	1099-0034-05R
	Chrome Plated S. S. Mesh Insert	1099-0040-05R
	Bottom Retainer	1099-0168-05
	(6) Rectangular Mesh Retainers	
	(7') Black Edge Guard	1999-0295-00
	(10) 3/16"x 1/2"x .062" Black Nylon Washers	1999-0256-00
	(14) 8-32 S.S. Hex Nuts	
	Small "E&G Classics" Emblem	
1	Hardware Kit (components listed below)	1099-1902-05
	(6) 1.006" x .189" x .064" Black Washers	1999-0264-00
	(6) #8-32 ESNA Half Nuts	
	(1) Hole Drilling Template	
	(1) S.S. Emblem Surround	
	(1) Double Faced Tape for Emblem	
	(1) E&G Multi-Color Emblem	1099-0046-05

Quantity	Description	<u>Part No.</u>
1	"Euro" Mesh Grille Insert (includes) _	*******
	"Euro" Chrome Plated Surround	1099-0037-05R
	Chrome Plated S. S. Mesh Insert	1099-0040-05
	Bottom Retainer	1099-0168-05
	(6) Rectangular Mesh Retainers	1099-0167-05
	(7') Black Edge Guard	1999-0295-00
	(10) 3/16"x 1/2"x .062" Black Nylon Washer	s1999-0256-00
	(10) 3/16"x 1/2"x .062" Black Nylon Washer	s1999-0256-00

"Euro" Part # 1099-0103-05R

1999-0295-00
1999-0256-00
1999-9072-00
1999-0268-00
1099-1902-05
1999-0264-00
1999-0065-00
1099-0039-05
1099-0044-05
1099-0197-05
1099-0046-05

Center Bar" Part # 1099-0104-05CBR

Ouantity	<u>Description</u>	Part No.
1	"Center Bar" Mesh Grille Insert (includes)	********
	"Center Bar" Chrome Plated Surround	1099-0038-05R
	Chrome Plated S. S. Mesh Insert	
	Bottom Retainer	1099-0168-05
	(6) Rectangular Mesh Retainers	1099-0167-05
	(7') Black Edge Guard	
	(10) 3/16"x 1/2"x .062" Black Nylon Washers	
	(14) 8-32 S.S. Hex Nuts	
	Small "E&G Classics" Emblem	
1	Hardware Kit (components listed below)	
	(6) 1.006" x .189" x .064" Black Washers	
	(6) #8-32 ESNA Half Nuts	
	(1) Hole Drilling Template	
	(1) S.S. Emblem Surround	
	(1) Double Faced Tape for Emblem	1099-0197-05
	(1) E&G Multi-Color Emblem	1099-0046-05

CNC "Ultimate" Mesh Part #	1099-0104-05A
Quantity <u>Description</u>	<u>Part No.</u>
1 Ultimate Mesh Grille Insert (inc	ludes):**********
Ultimate Aluminum Mesh Surroun	
Chrome PlatedStainless Steel Mesh	
Bottom Retainer	
(6) Restangular Mesh Retainers	
Ultimate Aluminum Top Emblem Sur	
Ultimate Aluminum Bottom Emblem	
(10) 3/16"x 1/2"x .062" Black Nylon W	
(18) 8-32 S.S. Hex Nuts	
Small "E&G Classics" Emblem	
1 Hardware Kit (components listed l	
(6) 1.006" x .189" x .064" Black W	
(6) #8-32 ESNA Half Nuts	
 Hole Drilling Template 	
 E&G Multi-Color Emblem 	1099-0046-05

Under no curcumstances is the removal of the front bumper cover required to install this grille.

Dual Weave Mesh Part # 1099-0104-05DR Description Quantity Part No. ******** Dual Weave Mesh Insert (includes) 1099-0034-05R Chrome Plated Surround Dual Weave Stainless Mesh Insert 1099-0040-05DR Bottom Retainer 1099-0168-05 1099-0167-05 (6) Restangular Mesh Retainers 1999-0295-00 (7') Black Edge Guard (10) 3/16"x 1/2"x .062" Black Nylon Washers 1999-0256-00 (14) 8-32 S.S. Hex Nuts _____ 1999-9072-00 Small "E&G Classics" Emblem 1999-0268-00 Hardware Kit (components listed below) 1099-1902-05 (6) 1.006" x .189" x .064" Black Washers 1999-0264-00 (6) #8-32 ESNA Half Nuts _____ 1999-0065-00 (1) Hole Drilling Template _____ 1099-0039-05 (1) S.S. Emblem Surround _____ 1099-0044-05 Double Faced Tape for Emblem _____ 1099-0197-05 E&G Multi-Color Emblem _____ ___ 1099-0046-05

"Fine" Mesh Part # 1099-0102-05R

Quantity	Description	Part No.
1	Fine Mesh Grille Insert (includes)	********
	Chrome Plated Surround	1099-0034-05R
	Chrome Plated S. S. Mesh Insert	1099-0020-05R
	Bottom Retainer	1099-0168-05
	(6) Rectangular Mesh Retainers	1099-0167-05
	(7') Black Edge Guard	1999-0295-00
	(10) 3/16"x 1/2"x .062" Black Nylon Washers	1999-0256-00
	(14) 8-32 S.S. Hex Nuts	
	Small "E&G Classics" Emblem	1999-0268-00
1	Hardware Kit (components listed below)	
	(6) 1.006" x .189" x .064" Black Washers	
	(6) #8-32 ESNA Half Nuts	
	(1) Hole Drilling Template	
	(1) S.S. Emblem Surround	1099-0044-05
	(1) Double Faced Tape for Emblem	1099-0197-05
	(1) E&G Multi-Color Emblem	1099-0046-05
1		

IMPORTANT!

The exposed edges of the stainless steel grille and mesh can be extremely sharp. Please handle with care.

	rt # 1099-0102-05ER					"BLACK ICE" Heavy M Part # 1099-B104-05	
Bottom Retainer (6) Rectangular Mesh R (7') Black Edge Guard (10) 3/16"x 1/2"x .062" B (14) 8-32 S.S. Hex Nuts Small "E&G Classics" E 1 Hardware Kit (compo (6) 1.006" x .189" x .00 (6) #8-32 ESNA Hali (1) Hole Drilling Tem (1) S.S. Emblem Surr	Nsert (includes) _ ********** Surround1099-0037-05R ert1099-0020-05 1099-0168-05 etainers1099-0167-05 1999-0295-00 ack Nylon Washers 1999-0256-00 1999-0268-00 1999-0268-00 nents listed below) 1099-1902-05 4" Black Washers 1999-0264-00 Nuts1999-0065-00 plate1099-0039-05 pound1099-0044-05 for Emblem1099-0197-05	" S B ((() () () () () () () () () () () ()	Description "Center Bar" Mesh Grille Insert (ind "Center Bar" Chrome Plated Surrou Stainless Steel Mesh Insert Bottom Retainer 6) Rectangular Mesh Retainers 7') Black Edge Guard 10] 3/16"x 1/2"x .062" Black Nylon W 14) 8-32 S.S. Hex Nuts Small "E&G Classics" Emblem Hardware Kit (components listed to 6) 1.006" x .189" x .064" Black W 6) #8-32 ESNA Half Nuts 1) Hole Drilling Template 1) S.S. Emblem Surround 1) Double Faced Tape for Emblem 1) E&G Multi-Color Emblem	Ind 1099-0038-05R 1099-0020-05CBR 1099-0168-05 1099-0167-05 1999-0295-00 'ashers 1999-0256-00 1999-0268-00 1999-0268-00 1999-0268-00 1999-0268-00 1999-0268-00 1999-0065-00 1999-0065-00 1099-0039-05 1099-0044-05 1099-0197-05	<u>Ouantity</u> 1		Part No. ************************************

Contrary to several popular websites, there are three mounting holes to be drilled in the lower portion of the bumper cover and six existing holes that need to be enlarged to 3/8" diameter. All holes are hidden by the grille once it is installed. Tools needed <

Flat blade screwdriver, 1/8", 3/8" & 3/32" drill bits, #2 & #3 square drive bits or #2 phillips screwdriver, sissors, awl or pointed tool, electric drill, masking tape, flat or semi-gloss black paint, 11/32" or 9mm deep socket, socket wrench, glass cleaner and a disc grinder (for tag bracket modifications).

Billet Grille Part # 1099	-0160-05R	"Ultimate" CNC Verticle B	illet Part # 1099-0160-05A	Important information before you begin:
Ouantity Description 1 Billet Grille (includes) Chrome Plated Surround w/Center Right Billet Insert Left Billet Insert	1099-016A-05	Ultimate CNC Verticle Bottom Retainer	Part No. le Billet (includes).********* Grille Section 1099-0161-05A 1099-0168-05 Retainers 1099-0167-05	This E&G grille installation kit includes grille hole location template(s) to drill mounting holes in the vehicle.
(4) Upper Retainers (1) Lower Retainer (7') Black Edge Guard (6) 3/16"x 1/2"x .062" Black Nylon W (14) 8-32 S.S. Hex Nuts	1099-0168-05 1999-0295-00 ashers 1999-0256-00 1999-9072-00	Ultimate Aluminum Top Ultimate Aluminum Bot (10) 3/16"x 1/2"x .062" E (18) 8-32 S.S. Hex Nut Small "E&G Classics" E	Emblem Surround 1099-0051-05A com Emblem Base_ 1099-0053-05A Black Nylon Washers 1999-0256-00 s 1999-9072-00 mblem 1999-0268-00	Before marking or drilling any holes into the vehicle, you MUST verify that the template(s) provided in this kit match the mounting pin
Small "E&G Classics" Emblem	1999-0094-00 Vashers 1999-3910-00 elow) 1099-1902-05 ashers 1999-0264-00	(6) 1.006″ x .189″ x .0 (6) #8-32 ESNA Hal (1) Hole Drilling Tem	nents listed below) 1099-1902-05A 64" Black Washers1999-0264-00 f Nuts 1999-0065-00 iplate 1099-0039-05 iblem 1099-0046-05	locations on the grille(s). Please place the assembled grille's mounting pins over the template(s) provided and make
 Hole Drilling Template	1099-0039-05 1099-0044-05 1099-0197-05	installations are	vn, all other grille exactly the same edure.	sure that the pin and hole locations are the same. If they do not match, please call: *** 1-410-381-4900 ***

Copyright © 2005 by E&G Classics, Inc.

and ask for technical assistance. Thank you.



factory grille to protect the paint (not shown).

access using a flat blade screw driver.

then remove the top plastic push fasteners that secure

the top of the bumper cover for factory grille fastener

2.

- Apply masking tape to the bumper cover around the Remove the four (4) factory fasteners (#2 square drive 3. bit) across the top and one (1) down each side of the Open the hood and remove the plastic header panel grille. covers (by lifting straight up, shown already removed),
 - 4. Unclip the top and the sides of the factory grille by pulling straight out (not shown).



The best way to remove the lower four (4) factory mounting screws is to use a small ratcheting screw driver or a ratching box wrench and a #2 square drive short bit (as shown). The large plastic screws that secure the bumper cover to the black bumper styrofoam need to be removed using a #3 square drive bit (not shown).

5.



6. Remove the lower four screws by pulling the grille out as far as you can for screw removal clearance. Remove the screws left to right, the subsequent screws will be easier to remove as you will be able to pull the grille farther out. **Removal tip:** If you can not access the lower screws, pull the factory grille out and straight up, working left to right, the lower four screws will simply pull through the very thin urethane bumper cover (lower holes not reused and are hidden by the mesh grille).



For vehicles other than ones painted black or dark col-7. ors: Mask the grille return edge 1/2'' back from the front of the opening and scuff the exposed paint with a scotch brite pad. Paint the return and, for all vehicles. everything that would be visible through the mesh grille with flat or semigloss black paint. Once the paint is dry, remove the masking tape.



Once the paint is dry, cut out, align and tape together the two piece template on the last page of this manual. Align the supplied template and tape it in place (as shown). Use an awl or similar pointed tool and mark the bumper cover at all mounting hole locations (see arrows).



- Drill through the marks made in the bumper cover with a 1/8" drill bit. Use the drill bit to make a slot between the 1/8" holes.
- Enlarge the top and side factory grille mounting holes to 3/8" (not shown). Enlarge the lower factory mount ing holes to 1/2" for E&G Grille stud clearance.



- Align the E&G grille into the opening and press the lower mounting studs into the holes drilled in the bumper cover to secure the bottom edge.
- Align the E&G Mesh Grille's center mounting studs with the enlarged factory mounting holes in the bumper cover before you align the upper mounting studs with the enlarged factory mounting holes.



 Once all top mounting studs are passed through the enlarged factory mounting holes, install black plastic washers and 8-32 ESNA lock nuts and tighten.

NOTE: If the top of the grille will not fit back into the opening, apply a liberal amount of glass cleaner across the top of the grille where it meets the bumper cover. Reach inside the bumper cover at the top and lift it up as high as possible. Have an assistant gently push the top of the grille into the opening to get it started, then allow the top fasteners to draw the grille into place as they are slowly tightened.



14. For all grilles except "Ultimate": Clean the top of the stain less surround and emblem surround with alcohol to remove grease & fingerprints. Install the supplied double faced tape ring to the back of the emblem surround. Align the E&G emblem surround. Peel back a small section of the double faced tape backing, align the emblem surround, pull out the tape backing and press the emblem surround firmly into place.



15. For all grilles: Make sure to thoroughly clean the emblem recess with alcohol to remove grease and fingerprints. Peel the backing from the E&G emblem and install the emblem in the center of the E&G emblem surround (or recess in the "Ultimate" grille).



16. Trim the front tag bracket (if equipped), removing the top mounting bosses and trimming the left and right extensions that originally fit into the front grille opening recess. When finished, the modified tag bracket should look this this.



- Align the modified front tag bracket below the mesh grille (where shown). Install the modified tag bracket back onto the bumper cover by drilling new 3/32" mounting holes and reusing the factory screws (DO NOT OVERTIGHTEN).
- **18**. Reinstall the factory bumper cover push pins and radiator support panel covers (not shown) to finish the installation.

WARRANTY INFORMATION:

E&G Classics, Inc. warrants its chrome parts and products to be free from defects in material, workmanship or finish for Thirty-Six (36) months from the date of shipment by E&G. This warranty is limited to the repair or replacement, at E&G Classics option, of the defective part or product. To obtain performance under this warranty you must:

- Present your E&G unit to an authorized distributor in your area with proof of purchase.
 If no distributor is available, contact E&G Classics (address below) for authorization to return unit.
- 3.) Returns All unauthorized returns will be refused. Merchandise approved by E&G for return must have been purchased within the Thirty-Six (36) months. All returns require an authorization number obtained from E&G and the actual return must be accompanied by the written authorization form filled out completely. All merchandise must be inspect ed upon receipt and shortages reported within 48 hours. All merchandise must be in a resalable condition. Merchandise must be packed carefully in the original packing. If original packing is no longer usable, repack item(s) comparable to original manner. All returns are subject to a 25% handling charge. Special order items are not returnable. Defective merchandise must have an explanation of the problem. No credit will be issued unless invoice number and date of purchase has been supplied. Manufacturer shall be sole judge of defects in a product.
- 4.) UPS accounts All returns must be prepaid. Do not send return shipments freight collect. Once E&G has made its decision and it is a claim against our warranty policy, E&G will credit incoming freight on damaged parts.
- 5.) No discontinued part or parts changed due to body style are returnable.

For Return Authorization, write or telephone: E&G Classics, Inc., 8910 McGaw Court, Columbia, MD 21045 (410) 381-4900 Attn.: Return Department

You are responsible for inspecting all packages containing E&G Classics' parts and product immediately upon their receipt and must file a claim with the carrier for any damage disclosure by such inspection and notify E&G classics in writing at the above address of any such damage. This warranty does not extend to any of our products which have been subject to misuse, neglect, accident or have been altered or repaired in any way. This warranty does not cover any accidental or consequential damages for any breach of this warranty agreement. E&G Classics shall have no responsibility for any loss of time, inconvenience, commercial loss or consequential damage, nor shall E&G be liable for any injury or damage to persons or property by reason of any defect in material, workmanship or finish of its parts or products. This warranty gives you specific legal rights and you may also have other rights which may vary from state to state.



Cut out, align and tape templates together.